

RIMS

Bobcat genuine rims are tested and validated to ensure proper fit on the machine and guarantee trouble-free service



RIMS

Bobcat genuine rims are tested and validated to ensure proper fit on the machine and guarantee trouble-free service without cracking, tire mounting issues or slippage under heavy use.



LOADERS RIMS SIZE GUIDE

Tires are designed to work best with corresponding internal rim width. Pairing the tire with the correct rim will ensure achieving the best loading capacity, traction, machine stability, tire life, protection and other parameters.

FOLLOW THIS SIMPLE GUIDE TO QUICKLY IDENTIFY THE RIM SIZE TO FIT THE MOST COMMON BOBCAT SKID STEER LOADERS TIRE SIZES.

TIRE SIZE	RIM DIAMETER	RECOMMENDED RIM SIZE (DIAMETER × WIDTH)
23 × 5.7–12	12	12 × 5
23 × 8.5–12		12 × 7
27 × 8.5–15	15	15 × 7
31 × 15.5 – 15 Super Float		15 × 13
10–16.5	16.5	16.5 × 8.25
12–16.5		16.5 × 9.75
13–16.5 Super Float		16.5 × 9.75
15–16.5 Super Float		16.5 × 12
14–17.5	17.5	17.5 × 10.5

OFFSET RIMS

Rim offset is the distance from the hub mounting surface to the center line of the wheel. The correct offset value is important for ensuring proper wheel fit on the machine. In addition to standard offset, some of the Bobcat rims for Loaders are also offered in an offset variant. Offset rims allow fitting wider, super float tires.

WHEN PAIRED WITH STANDARD WIDTH TIRES, OFFSET RIMS INCREASE MACHINE TRACK WIDTH FOR MORE STABILITY.



SKID STEER LOADERS RIMS						
RIM DIAMETER (")	RIM WIDTH (")	RIM SIZE	BOLT PATTERN	NOTE	PART NUMBER	MODEL
12	5	12 × 5	114 mm (4.5")		7225123	S70
		12 × 5	114 mm (4.5")		7225122	440; 443; 450; 453; 463
	7	12 × 7	114 mm (4.5")		7225125	S70
		12 × 7	114 mm (4.5")		7225124	440; 443; 450; 453; 463
15	6	15 × 6	152 mm (6")	Offset	7225126	S100
	8	15 × 8	152 mm (6")	No offset	6686872	S100
	7	15 × 7	203 mm (8")	For 7 × 15 tire 7245025	7267717	S450
	13	15 × 13	152 mm (6")		6658846	751; 753; 763; 773; 7753; 863; 873
		15 × 13	203 mm (8")		6561095	645; 653; 741; 742; 743; 751; 753; 773; 843; 853; 863; 873
16.5	8.25	16.5 × 8.25	152 mm (6")		6565237	630; 631; 632; 641; 642; 643
		16.5 × 8.25	203 mm (8")		7208252	S450; S510; S530; S550; S570; S590; S595
		16.5 × 8.25	203 mm (8")		7247451	S130; S450; S510; S530; S550; S570; S590; S595, S66
		16.5 × 8.25	203 mm (8")		7234460	S130; S150; S160; S450; S510; S530; S550; S570; S590; S595
		16.5 × 8.25	203 mm (8")	Offset	7232568	S130; S150; S160; S175; S185; S205; S510; S530; S550; S570; S590; S595
		16.5 × 8.25	203 mm (8")	Offset	7400550	S66
	9.75	16.5 × 9.75	203 mm (8")		7232567	S130; S150; S160; S175; S185; S205; S220; S250; S300; S510; S530; S550; S570; S590; S595; S630; S650; S76
		16.5 × 9.75	203 mm (8")	Offset	7232565	S220; S250; S300; S630; S650; S76
		16.5 × 9.75	203 mm (8")		7408135	S66
		16.5 × 9.75	273 mm (10.75")		7225127	A220; A300; A770; S750; S770
		16.5 × 9.75	273 mm (10.75")	Offset	7225128	S740; S750; S770
	12	16.5 × 12	203 mm (8")		6732847	S220; S250; S300; S630; S650; S76
		16.5 × 12	203 mm (8")		6728991	863; 873; 883; S250
		16.5 × 12	273 mm (10.75")		6729990	A220; A300; A770; S750; S770
17.5	10.5	17.5 × 10.5	273 mm (10.75")		7144829	S850





TELESCOPIC LOADERS RIMS			
RIM DIAMETER	NOTE	PART NUMBER	MODEL
17		6914892.0	T2556; T2566; V518; VR518
17.5		6920676.0	T2250; V417
20		6914895.0	T35100; T35100L; T35100SL; T35120L; T35120SL; VR530C; VR723
	−3 mm offset	7239290-0	TL26.60; TL30.60; TL30.70; TL358; V519
	+12.5 mm offset	7160212-0	TL34.65HF; TL35.70; TL360; TL38.70HF; TL470; TL470HF
22.5	Standard wheel	7021553	TR40250; TR40250 Evo; TR45190; TR50190 Evo; TR50210; TR50210 Evo
	Agri wheel	7014960	TR40250; TR45190; TR50210
24	+29 mm offset	7214831-0	T35.130S; T35.130SLP; T35.140S; T35130S; T35130SL; T35140S; T40.180SLP; T40140; T40170; T40180; T41.140SLP
	+12.5 mm offset	7160199-0	TL34.65HF; TL35.70; TL360; TL38.70HF; TL43.80HF; TL470; TL470HF; V723
	−3 mm offset	7239241-0	TL26.60; TL30.60; TL30.70; TL358
	+12.5 mm offset	7160199-G	TL34.65HF; TL35.70; TL360; TL38.70HF; TL43.80HF; TL470; TL470HF; V723
24	+12.5 mm offset	7188514-0	TL34.65HF; TL35.70; TL360; TL38.70HF; TL470; TL470HF
	+12.5 mm offset	7341102-0	TL43.80HF



BACKHOE LOADERS RIMS		
MODEL	NOTE	PART NUMBER
B700	Front (2WD)	7289989
	Front (4WD)	7289984
	Rear	7289981
B730; B53R11001 & Above; B53S11001 & Above; B53T11001 & Above	Front	7408569
	Rear	7408568
B730; B45111001 & Above; B4B611001 & Above B750; B45211001 & Above; B4BM11001 & Above	Front	7393494
	Rear	7291676
B750	Front (4WD)	7293063
B780	Front & Rear (4WD)	7293433



BE OM **EN OFFERT**

Klicka bara på **knappen** eller skanna **QR-koden** nedan för åtkomst till vårt offertformulär.

Vi kontaktar dig så snart som möjligt. Tack!



BEGÄR OFFERT

